

July 23, 1993

ENSR Ref. No: 1620-013-600 ENSR Doc. No: 93191pm



ENSR Consulting and Engineering 4500 Park Glen Road Suite 210 St. Louis Park, MN 55416 (612) 924-0117 (612) 924-0317/FAX

Mr. James N. Grube
Director of Public Works
City of St. Louis Park
5555 Minnetonka Boulevard
St. Louis Park, MN 55466

Re: Work Plan for Sampling Coal Tar/Creosote-Impacted Soils

Dear Jim:

Per your request, ENSR is pleased to submit this work plan to collect additional soil samples from approximately 400 cubic yards of coal tar/creosote-impacted soil excavated in 1991 during the Trunk Highway 7 (TH7)/Louisiana Avenue Interchange construction project. The purpose of this project is to characterize the soil and arrange for its subsequent disposal. We anticipate treating the soil at a Northern States Power (NSP) facility in the Twin Cities area.

#### **BACKGROUND AND PREVIOUS SAMPLING RESULTS**

The City of St. Louis Park (City) encountered coal tar/creosote-impacted soils during construction of the above-mentioned intersection. Impacted soils encountered during that project were excavated and stored under impervious cover in a security area pending disposition.

The impacted soils resulted from the nearby operations at the Reilly Site. Reilly was a coal tar distillation/wood preserving plant which ultimately impacted a swamp immediately south of the site. The former swamp area is now the location of the interchange where the impacted soils were excavated.

During September 1991, the City collected a representative sample of the coal tar/creosote-impacted soils and submitted the sample to Interpoll Laboratories, Inc., for analysis. The sample was analyzed for hazardous waste characteristics, for toxicity characteristic leachate procedure (TCLP) for metals, polynuclear aromatic hydrocarbons (PAHs), and for volatile organic compounds (VOCs). Laboratory results indicate the sample was nonhazardous (Attachment 1).



July 23, 1993 Mr. James N. Grube Page 2

Į

í

In August 1992, the City collected eight soil samples from the four soil piles (two samples from each pile) for waste characterization per NSP's guidelines for accepting soils to be incinerated. Laboratory results (Attachment 2) indicate that the soil meets NSP's guidelines for accepting the soil for incineration.

During a previous sampling event (July 1991), two samples and one duplicate were collected as composite samples from the soil piles, and were analyzed for total PAH. The results indicate total PAH concentrations ranging from approximately 2500 to 8200 parts per million (ppm) (Attachment 3).

The soil sampling results to date generally indicate that the soil is nonhazardous and is suitable for treatment by incineration at an NSP facility. However, additional sampling is necessary to provide a consistent and complete characterization database representative of the entire 400 cubic yard volume of soil. The purpose of this work plan is to provide samples for complete characterization of the soil, in accordance with NSP and MPCA requirements, to obtain approvals for disposal, as planned.

#### SCOPE OF WORK

The overall sampling strategy will be to collect one composite sample for each 100 cubic yards of soil, for a total of four samples. The impervious plastic sheeting will be removed from the existing soil piles to allow for this sampling activity. A front-end loader will then be used to create four distinct soil piles, each of which will contain approximately 100 cubic yards of soil. this will allow better control of the soil, if a portion of the sample analytical results indicate disposal restrictions.

The composite samples will be collected from hand-auger borings taken in the four quadrants of each soil pile. Each boring will originate at the approximate mid-height of the soil pile and terminate at a depth of approximately 2 feet. Sample aliquots from the 2-foot depth will be placed in a stainless steel bowl for mixing and compositing. Mixing and distribution to sampling containers will be accomplished using a stainless steel spatula. All sampling equipment will be decontaminated between samples by scrubbing with a detergent water, and rinsing with deionized water.

The samples will be transported to Interpoll Laboratories in circle Pines, Minnesota, for analysis. Labeling and chain-of-custody procedures, which are consistent with ENSR's standard operating procedures, will be followed. The analyses will include:



July 23, 1993 Mr. James N. Grube Page 3

- Heat value
- Ash content
- Total moisture
- Hq •
- Lead
- Selenium
- Silicon
- Total fluorine

- Chlorine
- Bromine
- Fixed carbon
- Volatile matter
- Total polychlorinated biphenyls (PCBs)
- TCLP metals
- TCLP organics (volatiles and semivolatiles)

#### **HEALTH AND SAFETY**

The Reilly Site Health and Safety Plan will cover all work on this project.

#### SOIL DISPOSAL

Upon receipt of the analytical data for this project, NSP's Material Characterization Sheet (Attachment 4) will be completed and submitted to NSP for review. Following NSP's review, a brief report will be prepared to document the soil characterization results for MPCA and to request approval for treating this soil at a NSP facility in the Twin Cities area.

Based on recent history, the Allen S. King facility in Bayport, Minnesota, may be a poor choice for treating these soils due to public opposition to treating Minnegasco soils. Although the King plan is the only facility currently permitted to accept this type of material, NSP expects to re-permit two other area plants including the Black Dog facility in Burnsville, Minnesota. The Black Dog facility is the most likely choice for treatment once permitting is completed. It is hoped that this can be accomplished pursuant to either:

- The conditions of the new permit for alternate fuels, or
- Special approval for a one-time handling of the soil

Details on the selection of the NSP facility and on obtaining all necessary approvals for treatment in this manner will be identified pending successful completion of this sampling/analysis work plan.

If you have any questions regarding this work plan, please contact me.

Sincerely, //

William M. Gregg General Manager

# O interpoll

INTERPOLL LABORATORIES, INC. 4500 BALL ROAD.N.E. CIRCLE PINES, MINNESOTA 55014-1819

TEL: \$12/788-6020 FAX: 612/786-7854

October 25, 1991

City of St. Louis Park 5005 Minnetonka Blvd. St. Louis Park, MN 55416-2290

Attention: Jim Grube -

LABORATORY REPORT: #4295

SAMPLES COLLECTED: September 20, 1991 SAMPLES RECEIVED: September 20, 1991

Sample Identification: S-1
Sample Type: Soil
Laboratory Log Number: 4295-01

			Target Detection	
Parameter	<u>Units</u>	<u>Method</u>	<u>Limit</u>	
Alkalinity pH	mg/Kg	EPA 310.1 EPA 150.1	25	8900ª 7.9 <sup>b</sup>
Free cyanide	mg/Kg	4500-CNI <sup>c</sup>	0.2	< 0.2
Total solids	*	EPA 160.3	3	69
Reactive sulfide Free liquids	mg/Kg	(d) . SW-846, 9095	10	13
Total chlorine	* W/W	(e)	0.005	0.02
Flashpoint Bulk density	<sup>0</sup> F LB/FT³	ASTM D93 Gravimetric	2	> 200 79.17
Total PCB	mg/Kg	SW-846, 8080	0.0033	<0.0033

<sup>\*</sup>Contains no free liquids.

Sample Identification: Sample Type: Laboratory Log Number: S-1 Soil 4295-01

<u>Parameter</u>	<u>Units</u>	EPA Method	Target Detection <u>Limit</u>		
TCLP Leachate:					
Pheno1	mg/L	EPA 420.1	0.004		0.11
Arsenic	mg/L	SW-846, 6010	0.1	<	0.1
Barium .	mg/L	SW-846, 6010	0.01		1.3
Cadmium	mg/L	SW-846, 6010	0.01	<	0.01
Chromium	mg/L	SW-846, 6010	0.01	<	0.01
Lead	mg/L	SW-846, 6010	0.03		0.07
Mercury	mg/L	SW-846, 7470	0.0002	₽	.0002
Selenium	mg/L	SW-846, 6010	0.1	<	0.1
Silver	mg/L	SW-846, 6010	0.1	<	
Copper	mg/L	SW-846, 6010	0.01	<	0.01
Nickel	mg/L	SW-846, 6010	0.01		0.01
Zinc	mg/L	SW-846, 6010	0.01		1.6
TCLP Leachate:					_
o-Cresol	ug/L	SW-846, 8270	4.5		17
m+p-Cresol	ug/L	SW-846, 8270	4.5		
2,4-Dinitrotoluene	ug/L	SW-846, 8270	13	<	
Hexachlorobenzene	ug/L	SW-846, 8270	9.5	<	9.5
Hexachlorobutadiene	ug/L	SW-846, 8270	14	<	14
<b>Hexachloroethane</b>	ug/L	SW-846, 8270	6.0	<	6.0
Nitrobenzene	ug/L	SW-846, 8270	7.0	<	7.0
Pentachlorophenol	ug/L	SW-846, 8270	14	<	14
2,4,5-Trichlorophenol	ug/L	SW-846, 8270	8.0	<	8.0
2,4,6-Trichlorophenol	ug/L	SW-846, 8270	9.5	<	9.5

Sample	Identif	fication:
Sample	Type:	
Laborat	cory Log	Number:

S-1 Soil 4295-01

• •			Target Detection		
<u>Parameter</u>	<u>Units</u>	EPA Method	<u>Limit</u>		
TCLP Leachate:					
Benzene	ug/L	SW-846, 8240	1.0	<	2.0
Carbon tetrachloride	ug/L	SW-846, 8240	1.7	<	3.4
Chlorobenzene	ug/L	SW-846, 8240	1.0	<	2.0
Chloroform	ug/L	SW-846, 8240	1.0	<	2.0
1,4-01chlorobenzene	ug/L	SW-846, 8240	1.0	<	2.0
1,2-Dichloroethane	ug/L	SW-846, 8240	1.3	<	2.6
1,1-Dichloroethene	ug/L	SW-846, 8240	1.6	<	3.2
Methyl ethyl ketone	ug/L	SW-846, 8240	10	<	20
Pyridine	ug/L	SW-846, 8240	2000	<	4000
Tetrachloroethene	ug/L	SW-846, 8240	8.0	<	16
Trichloroethene	ug/L	SW-846, 8240	2.1	<	4.2
Vinyl chloride	ug/L	SW-846, 8240	1.6	<	3.2

Respectfully submitted.

Jeannie F. O'Neil, Manager Inorganic Chemistry Group

Wayne A. Olson, Manager Organic Chemistry Group

JFO/WAO/cg
Invoice Enclosed
< = less than
> = greater than

Dilution factor

Soil alkalinity measured in water.

Soil pH measured in water.

Standard Methods, 17th Edition.

dEPA Method SY-846, Chapter 7, Section 7.3.4.2.

Digestion by oxygen parr bomb; analysis by ion chromatography.

Sample extract was diluted by a factor of 2 due to matrix interferences. Reported values represent the concentration in the original undiluted sample, i.e., instrumental results were multiplied by the dilution factor prior to reporting. Target detection limits are given. The detection limit applicable to the sample may be obtained by multiplying the detection limit by the dilution factor.

All analyses were performed using EPA or other recognized methodologies. All units are on an "as received" basis unless otherwise indicated.



INTERPOLL LABORATORIES, INC. 4500 BALL ROAD N.E. CIRCLE PINES, MINNESOTA SS014-1819 TEL: 612/786-6020 FAX: 612/786-7854

August 24, 1992

City of St. Louis Park 5005 Minnetonka Blvd. St. Louis Park. Minnesota 55416

Attention: Jim Grube

LABORATORY REPORT: #6578

ILI QUOTATION: #920713JF001

SAMPLES COLLECTED: July 23: 1992 SAMPLES RECEIVED: July 24: 1992

Sample Identification: #1 #2
Sample Type: Soil Soil
Laboratory Log Number: 6578-01 6578-02

Target Detection Limit Uni ts Lead mg/Kg SW-846, 6010 11 20 Selenium . SW-846, 6010 20 20 20 mg/Kg Silicon 2 10 23 mg/Kg SW-846, 6010 Total fluorine 0.005 0.008 0.007 mg/Kg 300.0 Total chlorine 300.0 0.005 0.020 0.007 mg/Kg Total bromine mg/Kg. 300.0 0.010 . < 0.010 < 0.010 Fixed carbon Calculation 4.81 12.36 mg/Kg Volatile matter mg/Kg **ASTM D3175** 0.1 7.64 9.61 Total PCB SW-846, 8080 0.0033 <0.0033 €2.0033 mg/Kg

. Interpoll Laboratories, Inc. Laboratory Report #6578 City of St. Louis Park

INTERPOLL LABS

August 24, 1992 Page 2 of 3

					Stockp	11e
Sample Ident	Fication:				#3	#4
Sample Type:					So11	Soil
Laboratory Lo	og Number:	_	_		<u>6578-03</u>	<u>6578-04</u>
s			SDA Method	Target Detection Limit	e e e	. · ·
<u>Parameter</u>		<u>Units</u>	EPA Method	Limit		
Lead		.mg/Kg	SW-846, 60		43	41
elenium	•	mg/Kg	SW-846, 60		< 20	< 20
Silicon		mg/Kg	SW-846, 60		. 20	. 20
Total fluoring		mg/Kg	300.0	0.005	0.01	0.007
Total chloria		mg/Kg	300.0	0.005	0.02	0.006
Total bromine	<b>.</b>	.mg/Kg	300.0	0.010	< 0.010	< 0.010
Fixed carbon	•	mg/Kg	Calculation	•	12.69	16.84
Volatile mati	ter	mg/Kg	ASTM D3175	_	11.34	13.01
Total PCB		mg/Kg	SW-846, 80	60 0.0099	<0.0066 <sup>2</sup>	<0.0099
Sample Ident:Sample Type: ' 'aboratory Lo					\$tockp #5 . Soil 1	11e #6 . Soil 6578-06
aboratory L	59 (Minuse).1	•	• • • • •		<del>93/4 44</del>	<u> </u>
	• •	• :	•	Target Detection		
<u>Parameter</u>		<u>Units</u>	EPA Method			
Lead ·		mg/Kg	SW-846, 60	10 5	. 120	71.
Selenium		mg/Kg	SW-846, 60	10 20	<b>&lt;</b> 20	< 20
Silicon		mg/Kg	SW-846, 60		28	20
Total fluoria	re	mg/Kg	300.0	0.005	0.010	0.008
Total chloring	ne	mg/Kg	300.0	0.005	0.010	0.01
Total bromine	2	mg/Kg	300.0	0.010	< 0.010	< 0.010
Fixed carbon		mg/Kg	Calculation	n •	20.62	18.56
Volatile mati	ter	mg/Kg	<b>ASTM D3175</b>		16.42	13.88
Total PCB		mg/Kg	SW-846, 80	80 0.0099	<0.0099	<0.0099

Interpoli Laboratories, Inc. Laboratory Report #6578 City of St. Louis Park August 24, 1992 Page 3 of 3

				<u>Stockpile</u>	
Sample Identification Sample Type: Laboratory Log Number				#7 So11 <u>6578-07</u>	#8 Soil. 6578-08
			Target Detection		18 2 2 22
<u>Parameter</u>	<u>Units</u>	EPA Method	<u>Limit</u>		
Lead	.mg/Kg	SW-846, 6010	5	74	70
Selenium	mg/Kg	SW-846, 6010	20	< 20	< 20
Silicon .	mg/Kg	· SW-846, 6010	2	25	20
Total fluorine	mg/Kg	300.0	0.005	0.01	< 0.005
Total chlorine	mg/Kg	300.0	0.005	0.01	< 0.005
Total.bromine.	mg/Kg	300.0	0.010	0.01	< 0.010
Fixed carbon	mg/Kg.	Calculation.		10.77	18.06
Volatile matter	mg/Kg	ASTM D3175	0.1	15.67	10.54
Total PCB	mg/Kg	SW-846, 8080	0.0099	<0.0099	<0.0099

Respectfully submitted.

Jeannie F. O'Neil, Manager Inorganic Chemistry Group

Wayne A Olson, Manager Organic Chemistry Group

.JFO/WAO/sk
Invoice Enclosed
< = less than

<sup>a</sup>The Total PCB detection limit for this sample is 0.0066 mg/Kg.

All units are on an "as received" basis unless otherwise indicated.

08-06-1992

.Client: ENSR

Laboratory Log Number: 6578-01-1971

Sample Identification: SOIL STOCKPILE #1

#### Short Proximate Analysis WT &

.Parameter	Moisture & Ash Free	Moisture Free	As Received
Moisture, Total	•	•	7.95
A≤h		94.49	86.97
Sulfur	2.97	0.16	0.15
Heating Value, BTU/LB.	5416	299	275

Respectfully submitted,

08-06-1992

Client: ENSR

Laboratory Log Number: 6578-02-1972

Sample Identification: SOIL STOCKPILE #2

#### Short Proximate Analysis WT &

Parameter	Moisture & Ash Free	Moisture Free	As Received
Moisture, Total			16.08
Ash		91.68	76.93
Sulfur	0.98	0.08	0.07
Heating Value, BTU/LB.	. 2637	. , 219	184

Respectfully submitted,

### Fuel Laboratory (612) 786-6020

08-06-1992

Client: ENSR

Laboratory Log Number: 6578-03-1973

Sample Identification: SOIL STOCKPILE #3

#### Short Proximate Analysis WT &

Parameter	Moisture & Ash Free	Moisture Free	As Received
Moisture, Total .			14.76
Ash		87.27	74.38
Sulfur	1.45	0.18	0.16
Heating Value, BTU/LB.	<u>.</u> 5519	<b>703</b>	599

Respectfully submitted.

08-06-1992

Client: ENSR

Laboratory Log Number: 6578-04-1974

Sample Identification: SOIL STOCKPILE #4

#### Short Proximate Analysis WT \*

Parameter	Moisture & Ash Free	Moisture Free	As Received
Moisture, Total		•	21.79
Ash		87.51	68.44
Sul fur	1.03	0.13	0.10
Heating Value, BTU/LB.	6560	819 -	. 641

Respectfully submitted.

08-06-1992

Client: ENSR:

Laboratory Log Number: 6578-05-1975

Sample Identification: SOIL STOCKPILE #5

#### Short Proximate Analysis WT &

Parameter	Moisture & Ash Free	Moisture Free	As Received
Moisture, Total			19.15
Ash		75.77	61.26
Sulfur	1.02	0.25	0.20
Heating Value, BTU/LB,	12953	3139	. 2538

Respectfully submitted.

08-06-1992

Client: ENSR

Laboratory Log Number: 6578-06-1976

Sample Identification: SOIL STOCKPILE #6

#### Short Proximate Analysis WT &

Parameter	Moisture & 'Ash Free	Hoisture Free	As <u>Received</u>
Moisture, Total			17.90
Ash		80.39	66.01
Sulfur ,	1.10	0.22	0.18
Heating Value, BTU/LB.	9920	1945	1597

" 'Respectfully submitted.""

08-06-1992

'Client: ENSR

Laboratory Log Number: 6578-07-1977

Sample Identification: SOIL STOCKPILE #7

#### Short Proximate Analysis WT &

Parameter · · ·	Moisture & Ash Free	Moisture Free	As <u>Recelved</u>
Moisture, Total			9.19
Ash		79.17	71.90
Sul <i>f</i> ur	0.55	0.12	0.10
Heating Value, BTU/LB.	10628	2214	2010

Respectfully submitted.

08-06-1992

Client: ENSR

UG-24-92 MCN 15:10

Laboratory Log Number: 6578-08-1978

Sample Identification: SOIL STOCKPILE #8

#### Short Proximate Analysis WT &

Parameter	Moisture & Ash Free	Moisture Free	As Received
Moisture, Total			15.47
Ash		82.64	69.86
Sulfur	1.16	0.20	0.17
Heating Value, BTU/LB.	14908	2588	2188

Respectfully submitted.

NET Atlantic, Inc. Thorofare Division

Data Summary Table

PAH Screen Results St. Louis Park, MN

NET Lab_ID ************************************	Client Id	PAH ug/g dw		PAH ug/g dw weight
	Instrument Blank	<1.0	<1.0	<1.0
71878	SP-1	704.5	1816.8	2521.3
71879	SP-1B	1059.5	1785.7	2845.2
71880	SP-2	3233.8	4975.1	8209.0

OC Summary Table
Wet Weight Calculation

71878 Original Result
Duplicate Result
RPD

Group 1 Group 2 Total

PAH PAH PAH

570.0 1470.0 2040.0

550.0 1800.0 2350.0

3.6% 20.2% 14.1%

Northern States Power Company
Allen S. King Generating Plant

1103 King Plant Road, Bayport, Minnesota 55003 Telephone: (612) 731-5701 FAX: (612) 731-7305

#### **MATERIAL CHARACTERIZATION SHEET**

Has this	waste been	previously submit	ed to NSP-King to be burned?	Yes 🗆	No 🗆	Renewal 🗆
Generatin	g Plant in	A SAFE, ECONO	MICAL, and ENVIRONMENT	ALLY SOU	ND MANNER. To a	us material at NSP's Allen S. King consider your material for burning heet for incineration. The material
			s of Minnesota Rules 7045.0214,	-		
	(1)	-	erial as a nonhazardous material t			
	(2)	Request further i	nformation/analysis; <u>OR</u>			
	(3)	Reject your mate	rial for burning.			
				_		
A.		r Information:		E,	Physical Description Disposition:	
Address:	·:				State: Liquid 🗆	Organic ☐ Inorganic ☐ Solid ☐ Semisolid ☐
Wingers.				•	yering: Unilayer	
			***************************************			(%) Total Solid:%
Technical	Contact:					
Telephon	e Number:_	( ) -		Odor:		
•	_			Color/Ap	pearance:	
B.		Disposal Contrac				
Company	Name:			F.	Physical Properties	
Address:					alues 🗆	Range 🗆
		<del></del>				
<u></u>	Contact:_					
				Density (	ሌ/ <del>ስ</del> ላ	
Terebrou	e tantunet:		<del></del>	Viscosity	(ca):	(°F)
C.	MPCA In	volvement:		v 1200011y	(*P/	
	naterial bee	n disclosed as a h	zardous waste to either the	G.	Employee Hazards:	1
		ty hazardous waste		Fire Haza	rd (Flash Points):	
	Yes 🗆	No 🗆	•		Below 73°F	Below 100°F
Contact:_					Below 140°F	Above 200°F
		<u> </u>			Will not burn	
			a spill, was the MPCA	Reactivity		
		he clean up?: Yes			May detonate	Explosive
			<del></del>		Unstable	Normally Stable
Contact:	<del></del>		·		Stable	
General C	comments:_	<del></del>		Special H	azarus: Water reactivity	0-:4:
			<del>-</del>		Radioactive	_ Oxidizer
				Special W	andling Requirements	
			<del></del>	Special 11	enoung vedantements	` <del></del>
D.		Anterial Characte				
Wareliai	escription:			H.	Chemical Composit	ion by Mass (no trade names)
			<del></del>	44.		up to 100%; identify
How was	material ge	nerated?			•	greater than 1%)
						%
						%
Frequency		One Time	Continuous			%
If one um	e, Quantity	<b>!</b>				%
	Container	size:				
	Container	description:		•	<del> </del>	
If more th	an one time	e, Quantity:			<del></del>	%
	Frequency	` <u></u>				
	Container	5176:				% %
	Container	description:	<del></del>			
					·	
					<del></del>	
						<u> </u>
						<u> </u>
						<u> </u>

I.	Heavy Metals:				K.	Other Materials present.	. Check all that apply:
Test Cla	ssification:	Total 🗆	TCLP Leachate		Asbestos:		
Units:		mg/kg 🛚	mg/liter 🗆		Ash:		
Arsenic:	·				Benzene:		
Berium:				<u> </u>	Non-comb	ustibles:	
Cadmius	m:			<u> </u>	Sludges:		
Chromit	im:				Toluene:		
Lead:					Xylene:		
Mercury	:			_	Waste Oil:		
Silver:_					Antifreeze	·	
Seleniun	n:			_			
Other:				_			
				_			
				_			
				_		Attachments:	
,			<del>_</del> -		Lab Analy	sis:	
J.	Halogens, Nitrog				TCLP Lea	chate:	
Total we	ight % Halogens:			%	MSDS:		
	Chlorine:	%	Bromine:	%	Other:		
	Fluorine:	%	Iodine:	%			
Total we	ight % Nitrogen:			%			
Total we	ight % Sulfur:			%			
м.	Certification:						
MI.	Ceruicadon:						
A4 an au	thorized segmentati	ue of the sens	stor I hemby cesti	fy that the i	oformation al	hove including attachment	s, are complete and accurate
							properties exists, and that all
							burning should the process
	g the waste change s						butming atouts the process
processi	E nio mano cumileo s	igminently of	which requestes by			sompany.	
Authoriz	ed Signature:					····	
Name (T	'ype of Print):						
							<del></del>
Date:			<del></del>		···	v	· · · · · · · · · · · · · · · · · · ·
Commen	lts:						
						<del></del>	<del></del>
_							
							<del></del>
		<del></del>				<del></del>	
						·	<del></del>
					<del></del>		·
Dieges ei	on and data the comit	fication Yes-	a conv for vove	ords and ex	and the origin	el material characterizatio	n sheet to:

Please sign and date the certification. Keep a copy for your records and send the original material characterization sheet to:

Northern States Power Company Fuel Resources Department 512 Nicollet Mall, 10th Floor Minneapolis, Minnesota 55402 Telephone: (612) 330-7581 FAX: (612) 330-7671

In addition, please send a copy of the material characterization sheet to:

Northern States Power Company
Environmental and Regulatory Affairs Department
414 Nicollet Mall, 2nd Floor
Minneapolis, Minnesota 55401
Telephone: (612) 330-7873
FAX: (612) 330-6357



### **ENSR Consulting and Engineering**

Alabama	Florence	(205) 740-8240			
Alaska	Anchorage	(907) 276-4302			
California	Los Angeles				
	Camarillo	(805) 388-3775			
•	Newport Beach	(714) 476-0321			
	San Francisco	(415) 865-1888			
Colorado	Fort Collins	(303) 493-8878			
Connecticut	Hartford	(203) 657-8910			
Illinois	Chicago	(708) 887-1700			
Massachusetts	Boston	(508) 635-9500			
Minnesota	Minneapolis	(612) 924-0117			
New Jersey	Mahwah	(201) 818-0900			
·	New Brunswick	(908) 560-7323			
Pennsylvania	Pittsburgh	(412) 261-2910			
South Carolina	Rock Hill	(803) 329-9690			
Texas	Dallas	(214) 960-6855			
	Houston	(713) 520-9900			
Washington	Seattle	(206) 881-7700			
Puerto Rico	San Juan	(809) 769-9509			